This listing of claims will replace all prior versions and listings of claims in the application:

Listing of Claims

- 1. (amended) A printer having a plurality of print media paths therethrough, said printer further comprising:
 - (1) a printer device;
- (2) a first print media path that carries a sheet of print media from a sheet pickup mechanism to the printer device;
- (3) a second print media path that carries the sheet from the printer device to a sheet exit opening;
- (4) a third print media path that carries the sheet from the sheet exit opening back to the printer device;
 - (5) a housing having:
- (a) at least one sheet entry opening through which a sheet can be delivered to the first print media path, and
- (b) at least one sheet exit opening through which the sheet can be dispensed from the housing after said sheet travels, in a first flow direction, past the printer device and a sheet diverter;
- (6) the sheet diverter having a first operating position for allowing the sheet to pass, in the first flow direction, and a second operating position for diverting the sheet while said sheet travels in a second flow direction[,] toward the printer device; and
- (7) a sheet pickup mechanism having a first operating position wherein said <u>sheet pickup</u> mechanism picks up the sheet from a sheet dispensing tray, and a second operating position wherein said mechanism serves as a part of a duplex printing path when the sheet travels in the second flow direction[,] toward the printer device.
- 2. (original) The printer of claim 1 wherein the housing has at least two sheet entry openings through which a sheet can be delivered for transport to the printer device.
- 3. (original) The printer of claim 1 wherein the housing has three sheet entry openings through which a sheet can be delivered for transport to the printer device.
- 4. (cancelled)

- 5. (amended) The printer of claim 1 wherein the sheet diverter is pivotally mounted so that, in its first operating position, a sheet traveling in the first flow direction, will not collide with said diverter and so that, in its second operating position, a sheet traveling in the second flow direction will collide with said sheet diverter and be diverted toward the printer device.
- 6. (original) The printer of claim 1 further comprising a sheet collection tray that services the sheet exit opening.
- 7. (original) The printer of claim 1 further comprising two sheet dispensing trays that are each serviced by a separate and distinct sheet pickup mechanism.
- 8. (original) The printer of claim 1 wherein a second sheet entry opening, the printer device and the sheet exit opening are on substantially the same horizontal plane such that a sheet passing over said horizontal plane is not bent more than about 30°.
- 9-16 (cancelled)
- 17. (amended) A method for increasing the versatility of a printer, said method comprising:
 - (1) locating a printer device in a printer housing;
- (2) providing a plurality of media paths that pass through the printer housing and printer device;
- (3) providing at least one sheet entry opening through which a sheet can be delivered to the printer device;
- (4) providing the housing with [(a)] at least one sheet exit opening for (1) dispensing a sheet from the housing when said sheet travels past the sheet diverter in a first flow direction and (2) permitting a sheet to travel past the sheet diverter in a second flow direction leading back toward the printer device;
- (5)[(4)] positioning a sheet diverter in the housing such that, while in a first operating position, the <u>sheet</u> diverter can facilitate passage of the sheet out of the <u>sheet</u> exit opening and such that, while in a second operating position, the <u>sheet</u> diverter can direct the sheet in a second flow direction toward the printer device; and
- (6)[(5)] positioning a sheet pickup mechanism in the housing such that, in a first operating position, said sheet pickup mechanism drives a sheet toward the printer device and such that, in a second operating position, said sheet pickup mechanism serves as a part of a